



## Material Safety Data Sheet

# Acrylic One Retarder

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

**Product name:** Acrylic One Retarder

**Supplier:** Acrylic One  
Nijverheidsweg 15 A  
3251 LP Stellendam  
+31-187-663006  
[info@acrylicone.com](mailto:info@acrylicone.com)

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

NO.	CAS REG No.	Weight %
1. Ammonium salts of acrylic polymer	Not Hazardous	5-95
2. Residual monomers	Not required	<0,05
3. Water	7732-18-5	5-95

This Product is a preparation.

### 3. HAZARDS IDENTIFICATION

Primary Routes of Exposure: Inhalation, Skin contact and Eye contact.

Inhalation: Inhalation of vapour or mist can cause the following:  
Headache, nausea, irritation of the nose, throat and lungs.

Skin contact: Prolonged or repeated skin contact can cause the following:  
Slight skin irritation.

Eye Contact: Direct contact with material can cause the following:  
slight irritation.

Delayed effects: Prolonged or repeated overexposure to dusts or mists can cause lung irritation.

#### 4. FIRST AID MEASURES

Inhalation: Move subject to fresh air.

Skin Contact: Wash affected skin areas thoroughly with soap and water consult a physician if irritation persists.

Eye Contact: Flush eyes with a large amount of water for at least 15 minutes. Consult a doctor if irritation persists.

Ingestion: If swallowed, give 2 glasses of water to drink. Consult a doctor. Never give anything by mouth to an unconscious person.

#### 5. FIRE-FIGHTING MEASURES

Flash Point:	Non-combustible
Auto-ignition Temperatures	Not applicable
Lower Explosive Limit	Not applicable
Upper Explosive Limit	Not applicable

Unusual Hazards: Material can splatter above 100 °C. Dried product can burn.

Extinguishing Agents: Use extinguishing media appropriate for surrounding fire

Personal Protective Equipment: Wear self-contained breathing apparatus and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Protection: Appropriate protective equipment must be worn. When handling a spill of this material. See SECTION 8, exposure Controls / Personal Protection for recommendations. If exposed to material during clean up operations, see Section 4, First Aid Measures, for actions to follow.

Procedure: Keep spectators away. Floor may be slippery; use care to avoid falling. Contain spills immediately with inert materials (e.g. sand, earth). Transfer liquids and solid diking material to separate suitable containers for recovery or disposal.

Caution: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

#### 7. STORAGE AND HANDLING

Storage Conditions: Keep from freezing: material may coagulate. Minimum recommended storage temperature for this material is 1 °C.

Maximum recommended storage temperature for this material is 49 °C

Handling Procedures: Monomer vapours can be evolved when material is heated during processing operations. Note: Formaldehyde will be generated under acidic conditions. Maintain adequate ventilation under these conditions to prevent exposure to formaldehyde above the recommended ceiling of 0.3 ppm.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

No.	CAS REG NO	Weight %
1. Ammonium salt of acrylic polymer	Not Hazardous	0-50
2. Residual monomers	Not required	< 0.05
3. Water	7732-18-5	0-50

Respiratory protection: a respiratory protection program must be followed whenever workplace conditions warrant a respirator's use. None required if airborne concentrations are maintained below the exposure limit. For dust or mist up to 5 times the exposure limit, wear a properly fitted approved filtering face piece. If oil mist is present, wear a single use filtering face piece.

Eye protection: Use approved safety glasses with side shields. Eye protection worn must be compatible with respiratory protection system employed.

Hand protection: Neoprene gloves may provide protection against permeation.

Engineering controls (ventilation): Use local exhaust ventilation with a minimum capture velocity of 0.75 m/sec. at the point of dust or mist evolution.

Other protective equipment: Facilities storing or utilizing this material should be equipped with an eyewash facility.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Colour :	Light yellow
Appearance :	Clear
State :	Liquid
pH :	6 – 7
Specific Gravity :	1.10 – 1.25
Vapour Density :	< 1 water
Vapour Pressure :	17 mm Hg 20 °C water
Melting point :	0 °C water
Boiling point :	100 °C water
Solubility in water :	Completely soluble
Percent Volatility :	90 to 91 % water
Evaporation rate :	< 1 water

Physical and chemical data given are typical values for this product and are not intended to be product specifications.

## 10. STABILITY AND REACTIVITY

Instability: This material is considered stable. However, avoid temperatures above 230 °C, the onset of polymer decomposition. Thermal decomposition is dependent on time and temperature.

Hazardous Decomposition Products: Thermal decomposition may yield acrylic monomers.

Hazardous Polymerisation: Product will not undergo polymerisation.

Incompatibility: There are no known materials which are incompatible with this product. Instability

## 11. TOXICOLOGICAL INFORMATION

Toxicity data for a compositionally similar material:

Oral LD50 – rat	>5000 mg/kg
Dermal LD50 – rabbit	>5000 mg/kg
Skin Irritation – rabbit:	Practically non-irritating
Eye Irritation – rabbit:	Inconsequential Irritation

## 12. EXOLOGICAL INFORMATION

No applicable Data

## 13. DISPOSAL CONSIDERATIONS

Procedure: For disposal incinerate this material at a facility that complies with local state and federal regulations for handling reactive material.

## 14. TRANSPORT INFORMATION

Hazardous class : Not Regulated for Transport

## 15. REGULATORY INFORMATION

EEG

This product satisfies all the requirements of the European inventory of Existing Chemical Substances (EINECS)

Hazardous class : Not Regulated for Transport

## 16. OTHER INFORMATION

None

### DISCLAIMER OF LIABILITY

The information in this MSDS was obtained from sources we believe are reliable. However, this information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and maybe beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS may not be acceptable.